



MESK SPORTS focuses on quality and healthy sports. All products have passed EN or ASTM standards tested by SGS, TUV, INTERTECK and other third party inspection institutions to meet different requirements.

PVC Sports flooring

PVC sports flooring is widely used for sports courts with good wear resistance, skid resistance, resilience and so on.


PVC sports flooring is formed by polymer synthesis technology. Besides the advantages mentioned above, the flooring also has features of environmental protection, pressure resistance, shock absorption, moisture resistance, antibacterial activity with long service life. PVC sports flooring can make sports simple and happier.





Indoor Sports PVC										
Image	Surface	Normal size	Color							
	Wooden Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m	Optional Or Customized							
	Litchi Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.42m/1.5m Length: 15m/20m	Optional Optional Or Customized							
	Snake skin Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m	Optional Optional Optional Or Customized							
	Weave Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m	Optional Septiment of the septiment of							
	Gemstone Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m	Optional Septiment of the septiment of							






Outdoor PVC Series										
Image	Surface	Normal size	Color							
	Gem Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m								
	Wavy Pattern	Thickness: 4.5mm ~ 8mm or customized Width: 1.5m/1.8m Length: 15m/20m								
	Coarse gravel Pattern	Thickness: 6mm ~ 8mm Width:1.5m/1.8m Length: 15m/20m								









Technical Data Sheet											
Description	Test Method		Unit			Test	Test Result				
Roll Length	EN426		m	m			15/20				
Roll Width	EN426		m	m		1.42/1.5/1.8					
Total Thickness	EN428		m	mm		3.0-10					
Layer Thickness	EN429		m	mm		0.45-0.8					
Weight	EN430		Kg/m ²			2.8-5.5					
Technical Characteristics											
Test items		Test method									
Impact Treatment		Stain resistance			UV treatment						
Impact Resistance		DIN18032 N/M			≥0.8						
Abrasion Resistance		≤10		≤10		7					
Indentation Resistance		EN1516		mm		≤6					
Sound Insulation		ENISO717-2		dB		20-30					
Ball Bounce		DIN18032		%		≥98					
Friction Coefficient		-		0.45-0.65		0.59					
Rebound Coefficient		- ≥0.89		≥0.85	0.86		.86				
Sport Characteristics											
Test Items		Unit			Test Result						
Hardness		Shore A			75						
Rebound Values		%			12						
Tensile Strength		Мра			3.4						
Elongation At Break		%			153						
Flame Retardant		class			1						
Chemical Test											
Test Items		Unit	Te	chnical	Test result		Single				
			Re	equirements			determination				
Benzene		g/kg	≤0.05		0.02		eligible				
Methylbenzene +		g/kg		0.05	-		eligible				
Dimethylbenzene											
Floating toluene two different cyanic acid		g/kg <0.05		-		eligible					
Soluble Cadmium Limits		Mg/m²			0.03						
Volatile Content		g/kg			6						
Vinyl Chloride Monomer		mg/m²			-						
Soluble Pb Limit		Mg/m²			0.45						



Applications

Basketball, Badminton, Gym, Dancing room, Volleyball, Tennis, Table tennis, handball, Yoga, martial art Museum, Judo, Taekwondo and any kind of sports Courts.















Factory:









